

Forum+

Product and Technical Information

Class		EN 685 - DOM Domestic	23
		EN 685 - COM Commercial	32
Wearlayer		EN ISO 24340 EN 429	0,5 mm
Total Thickness		EN ISO 24346 EN 428	2,0 mm
Total Weight		EN ISO 23997 EN 430	1250 gm/m ²
Standard Width		EN ISO 24341 EN 426	2 m
Standard Length		EN ISO 24341 EN 426	25 m
Residual Indentation		EN ISO 24343-2 EN 433	≤ 0,10 mm
Recation to Fire		EN ISO 9239-1	CRF 8.6
Dimensional Stability		EN ISO 23999 EN 432	≤ 0,40 %

R POLYSTYL has developed **R-Max**, a new wear layer surface treatment using reinforced polyurethane combined with Aluminum Oxide. Aluminium Oxide is the third hardest substance after Diamond and Carbon. Therefore **R-Max** has a wear resistance 3 to 4 times greater than polyurethane. **R-Max**, thanks to its hardness avoids scuff marks, eases maintenance, increases durability and protects the appearance of the flooring.

Installation - Preparing the Floor

The sub-floor must be smooth, dry perfectly even and free of any containments i.e. grease, paint, oil etc.. If the surface is not absolutely even we recommend a suitable floor levelling compound be used to remove any undulations.

General Recommendations

We recommend to unroll and relax the material for 24 hours before installation. Do not lay the material at a room temperature lower than 15° C.. Before laying the vinyl check the match of the different sheets of vinyl. Seams will be less visible if the strips are laid perpendicular to light source (windows). Leave a gap of 1 mm between the material and the walls or all the over vertical surfaces.

Glueing

The material should be adhered all over with an acrylic dispersion adhesive and spread with notched trowel 1.6 mm "V" notch (carefully respect the instructions of glue manufacturers). To obtain a good adhesion of the material to the sub-floor, you can press all the surface with a rubbing board—starting from the middle of the room. It is necessary to seal the seams with a cold welding system, as with the case of loose laying. Recommended adhesives: **Roberts GS200** or **UZIN KE2000**.

Note: Do not place heavy items or furniture directly onto flooring for 12 to 24 hours after glueing whilst glue is curing.

Maintenance

A correct maintenance regime will enhance the life expectancy and appearance of your flooring. Avoid surface scratches by sweeping or vacuuming your floor as often as necessary to remove loose dirt. Weekly maintenance is by way of mopping/washing the floor with luke warm water, a recommended neutral detergent or floor cleaner and rinse with clean water.

Light Stability		EN ISO 105 B02	≤ 6°
Chemical Resistance			Ok
Impact Sound Improvement		EN ISO 717/2	Δ Lw 15 dB
Abrasion Group		EN 660-1	T
Castor Chair		EN ISO 4918 EN 425	Suitable
Underfloor Heating		EN 12667	Suitable
Slip Resistance		AS 4586:2013	R10 (P3)
Electrical Behavior		EN 1815	2 kV
Recyclability			Ok
Guarantee			15 Years

Remove Stains

It is possible to remove stains with pure floor cleaner. Do not use solvents. In case of tar and other stubborn marks, clean with white-spirit if necessary.

Particular Care

- Do not use wax;
- Protect furniture and chair legs with plastic or felt tips since wax may migrate;
- Do not use rubber wheels and pads;
- If using caster chairs ensure suitable caster chair mats are used; and
- Do not lay the material in a room where chemicals are used.

The POLYSTYL Guarantee

POLYSTYL grant a guarantee for a period of 15 years on their cushioned vinyls starting from the date of purchase by the customer. The guarantee is valid for products which have been laid and maintenance according to our instructions and only for products in residential use. Each compliant will have to include a sample showing defect or to be inspected by a person appointed by POLYSTYL. In the event of a justified complaint, POLYSTYL will replace the floorcovering free of charge in proportion to the remaining period of the guarantee.

Example: 100% for ≤ 2 years;
80% for ≤ 4 years;
60% for ≤ 6 years;
40% for ≤ 10 years.
20% for ≤ 15 years.

If the floor covering is not available anymore, POLYSTYL will supply the most similar item in their ranges. The guarantee does not cover the consequences of bad maintenance, incorrect laying, damages, the action of chemicals, the discolouration due to contact with rubber and latex carpet backing and with tar in passages and generally all other cases which do not correspond to our instructions. The guarantee may not cover the pulling up and the laying of the material and the transport costs on a pro-rota sliding scale of above warranty period. To make a claim under this guarantee, take the proof of purchase to the store where you purchased the product for further inspection and approval. PR Floors will pay your reasonable direct expenses of claiming under this guarantee. You may submit details and proof of your claim to PR Floors for consideration. This guarantee is provided in addition to the other rights and remedies you may have under law; our goods come with guarantees which cannot be excluded under the Australian Consumer Law. You are entitled to replacement or refund for a major failure and to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure, and for compensation for any other reasonably foreseeable loss or damage.

This warranty is given by: **PR Floors Pty Ltd**, ABN 44009964658
21 Computer Road, Yatala QLD 4207
Ph: 07 3807 4422



PR.FLOORS

Ph: 07 3807 4422
www.prfloors.com