

Product standard: EN ISO 10582 = Heterogeneous resilient floorcovering in planks and tiles

PRODUCT SPECIFICATIONS	STANDARD	ECO 30
Product standard	EN ISO 10582	Heterogeneous resilient floorcovering
Total thickness	EN ISO 24346	2,0 mm
Wear layer thickness	EN ISO 24340	0,30 mm
Classification	EN ISO 10874	Domestic: 23 Commercial: 31
Total weight	EN ISO 23997	3.300 g/m ²
Abrasion group	EN 660-2	Group T: ≤ 2,00 mm ³ Planks: 177,8 x 1219,2 mm 22 planks/box = 4,77m ² 60 boxes/pallet = 286,2m ²
Dimensions	EN ISO 24342	
Surface treatment	-	PUR Ecoprotect™
Edges	-	No bevel

PRODUCT PERFORMANCES	STANDARD	ECO 30
Dimensional stability	EN ISO 23999	≤ 0,10 %
Castor chair	ISO 4918	No damage
Furniture leg	EN ISO 16581	No damage
Squareness & straightness	EN ISO 24342	≤ 0,25 mm
Residual indentation	EN ISO 24343-1	≤ 0,10 mm
Impact sound reduction	EN ISO 717-2	ΔLw = 6 dB
Light fastness	EN ISO 105-B02	≥ 6
Slip resistance	DIN 51130 EN 13893	R10 DS
Resistance to chemicals	EN ISO 26987	Not affected (0)
Thermal resistance	EN ISO 1045	0,01 m ² K/W
Fire resistance	EN 13501-1	B _{f,r} ≤ 1
Resistance against staining	EN 26987	Passed

ENVIRONMENT	STANDARD	ECO 30
TVOC after 28 days (AgBB test) - Indoor air quality	ISO 16000-9	≤ 100µg/m ³
VOC emission class (French regulation) - Indoor air quality	ISO 16000-9	A+
Floorscore VOC test - Indoor air quality	ISO 16000-9	Passed
Plasticiser	-	Phthalate-free
Formaldehyde group	EN 717-1	E1
Recyclability	-	100%

WARRANTIES		ECO 30
Residential warranty	-	10 years
Commercial warranty	-	5 years



Disclaimer: Images are for a reference guide only. Due to printing processes, images may vary from actual physical product.